

IX PFAS



IX WATER
ECO FILTRATION



INTRODUCING IX PFAS FOR PFAS REDUCTION

The IX PFAS cartridge is a refillable filter designed with advanced ion exchange media, specifically engineered for the removal of per- and polyfluorinated substances (PFAS). It delivers reliable removal of both short-chain and long-chain PFAS compounds that conventional filters, such as carbon, often fail to capture.

INTRODUCING IX PFAS

With proven effectiveness against seven of the most common contaminants — PFOS, PFOA, PFNA, PFHpA, PFHxS, PFBS and PFDA — the IX PFAS provides peace of mind for cafés, restaurants, offices, and other environments where safe, clean drinking water is critical. Compared with carbon filters, the IX PFAS offers up to twice the flow rate and up to ten times the capacity, making it a powerful and practical solution for environments where water quality matters.



SPEC SHEET

MODEL	CAPACITY*	DIMENSIONS (mm)
Medium	17,000 Litres	317 High X 167 Dia
Large	30,000 Litres	406 High X 167 DiA

* These capacities are based on controlled PFAS test water. In practice, naturally occurring substances (e.g. chloride, sulphate, nitrate, alkalinity) may reduce cartridge life, so actual service will vary with local water quality.

- Working pressure 1.5 - 6 Bar**
- Water inlet temperature 4 - 30°C - Only connect to a cold Food-Safe water supply
- Flowrate - up to 4 litres per minute***
- Nominal Flow Rates:
 - Medium - 2.4L / minute
 - Large - 4L / minute

For best results, flush the cartridge for at least five minutes before use. It is designed for cold water only, must be installed to local regulations, and the media is single-use. If chlorine levels exceed 2 ppm, pre-treatment is recommended.

** A pressure-reducing valve is recommended if the working pressure is greater than 3.5 bar.

THE IX HEAD

With the multi-stage variable bypass (5 options), you can tailor and control the product water to the required mineral level. Features a 5-stage filtration process that includes: Prefiltration, Silver Activated Carbon, sediment reduction, Media specific water treatment, Fine filtration.



Head connections inlet / outlet
3/8th push-fit

The IX Head has a built in easy to use flush valve and quick to change variable bypass.

Easy and quick change of the refill

IX ACCESSORIES



DM 3/8th STEM
3/8" BSP
DM-ASAB0606



3/8th - 3/8" BSP
STEM
DM-ATEU0606



3/8th - 3/4" BSP
STEM
EW1403



3/8th POLYETHYLENE
TUBE
DM-DPE06-BK



10 BORE 1MTR
BRAIDED HOSE
EW-C-HOSE-1.0-001



WALL MOUNT
BRACKET
IXBRACKET



WATER TEST KIT
ALK-TEST-KIT-80



FLOW PLAN WI-FI
USAGE MONITOR
FLOW-X-P